

45°


Design by Víctor Carrasco

45° fixture features a customised composition of vertical tubes that create a sculptural effect overhead. Suspended from the ceiling like sleek stalagmites, they create an array of glowing accent lighting points.

Ceiling



8250



Finishes <ul style="list-style-type: none"> ● 03/ __ White (RAL 9016) ● 04/ __ Black (RAL 9005) 	LED temperature colour <ul style="list-style-type: none"> /1 _ 2700 K E >90 1352,27 lm 101 lm/W /2 _ 3000 K E >90 662 lm 49 lm/W /3 _ 3500 K F >90 1463,02 lm 109,18 lm/W 	Control <ul style="list-style-type: none"> 8250 __ / _ 3 1-10V 8250 __ / _ 5 Push
---	---	---

Finishes <ul style="list-style-type: none"> ● 52/ __ Black oxide (Satin bronze) 	LED temperature colour <ul style="list-style-type: none"> /1 _ 2700 K E >90 1352,27 lm 101 lm/W /2 _ 3000 K E >90 662 lm 49 lm/W /3 _ 3500 K F >90 1463,02 lm 109,18 lm/W 	Control <ul style="list-style-type: none"> 8250 __ / _ 3 1-10V 8250 __ / _ 5 Push
---	---	---

Materials

Diffuser: Polycarbonate.
Tube: Aluminum.

Light Source and electronics

1 x LED 6,1 W 350 mA
Constant Current 350 mA
230V 50Hz


Packaging

1 Box 0,21 x 0,21 x 0,48 m
Vol 0,0211 m³
Gross weight 2,1 Kg Net weight 1,15 Kg


Notes

Surface fitting.
It includes interchangeable diffusers, mink or orange finishes

UNTIL STOCK RUNS OUT



8251



- Finishes**
- **03/** __ White (RAL 9016)
 - **04/** __ Black (RAL 9005)

LED temperature colour

/1 _ 2700 K E	CRI >90 1352,27 lm 101 lm/W
/2 _ 3000 K E	CRI >90 662 lm 49 lm/W
/3 _ 3500 K F	CRI >90 1463,02 lm 109,18 lm/W

- Control**
- 8251** __ / _ **B**
1-10V, Push
 - 8251** __ / _ **1**
DALI

- Finishes**
- **52/** __ Black oxide (Satin bronze)

LED temperature colour

/1 _ 2700 K E	CRI >90 1352,27 lm 101 lm/W
/2 _ 3000 K E	CRI >90 662 lm 49 lm/W
/3 _ 3500 K F	CRI >90 1463,02 lm 109,18 lm/W

- Control**
- 8251** __ / _ **B**
1-10V, Push
 - 8251** __ / _ **1**
DALI

Materials

Diffuser: Polycarbonate.
 Tube: Aluminum.

Light Source and electronics

1 x LED 6,1 W 350 mA
 Constant Current 350 mA
 110-240V 50/60Hz

Packaging

1 Box 0,21 x 0,21 x 0,48 m
 Vol 0,0326 m³
 Gross weight 2,9 Kg Net weight 1,95 Kg


Notes

Surface fitting.
 It includes interchangeable diffusers,
 mink or orange finishes

UNTIL STOCK RUNS OUT



8252



- Finishes**
- **03/** __ White (RAL 9016)
 - **04/** __ Black (RAL 9005)

LED temperature colour

/1 _ 2700 K E	CRI >90 1352,3 lm 101 lm/W
/2 _ 3000 K E	CRI >90 662 lm 49 lm/W
/3 _ 3500 K F	CRI >90 1463,02 lm 109,18 lm/W

- Control**
- 8252** __ / _ **B**
1-10V, Push
 - 8252** __ / _ **1**
DALI

- Finishes**
- **52/** __ Black oxide (Satin bronze)

LED temperature colour

/1 _ 2700 K E	CRI >90 1352,3 lm 101 lm/W
/2 _ 3000 K E	CRI >90 662 lm 49 lm/W
/3 _ 3500 K F	CRI >90 1463,02 lm 109,18 lm/W

- Control**
- 8252** __ / _ **B**
1-10V, Push
 - 8252** __ / _ **1**
DALI

Materials

Diffuser: Polycarbonate.
 Tube: Aluminum.

Light Source and electronics

1 x LED 6,1 W 350 mA
 Constant Current 350 mA
 110-240V 50/60Hz

Packaging

1 Box 0,19 x 0,13 x 1,265 m
 Vol 0,0312 m³
 Gross weight 6,25 Kg Net weight 4,75 Kg

Notes

Surface fitting.
 It includes interchangeable diffusers,
 mink or orange finishes

UNTIL STOCK RUNS OUT

