

Flamingo Mini

Design by Antoni Arola

Flamingo Mini creates multi-layered silhouettes with an avant-garde, intriguing aesthetic. This hanging lamp recalls a bird hovering overhead, bringing an intimate ambience as it casts diffuse gradations of soothing light through its translucent diffuser.

Pendants

1575

Ø 45 cm

1580

Ø 9 cm

1585

Ø 45 cm

1590

Ø 45 cm

Option A

Option B


Option C



Three options of installation



1575



Finishes
 ● 11/ _ _ Black (NCS S 8500-N)

LED Colour Temperature
 /1 _ 2700 K CRI >90 726 lm 124 lm/W

Control
 1575 _ _ / _ 1 DALI-2
 1575 _ _ / _ B Push; 1-10V
 1575 _ _ / _ Z Casambi

Materials
 Diffuser: PMMA. Rods: Stainless steel.
 Body: Aluminum. Canopy: ABS.


Light Source and electronics
 2 x LED 3W 175 mA
 Constant current 350 mA
 110-240Vac 50/60Hz

Packaging
 2 Boxes
 Box 1: 0,07 x 0,07 x 1,25 m
 Box 2: 0,51 x 0,51 x 0,16 m
 Total Vol 0,0478 m³
 Gross weight 5,5 Kg Net weight 4 Kg

Notes
 Additional cable length personalisation

Select Electrical connection Surface _23 Built-in XS

1580



Finishes
 ● 11/ _ _ Black (NCS S 8500-N)

LED Colour Temperature
 /1 _ 2700 K CRI >90 726 lm 124 lm/W

Control
 1580 _ _ / _ 1 DALI-2
 1580 _ _ / _ B Push; 1-10V
 1580 _ _ / _ Z Casambi

Materials
 Diffuser: PMMA. Rods: Stainless steel.
 Body: Aluminum. Canopy: ABS.


Light Source and electronics
 2 x LED 3W 175 mA
 Constant current 350 mA
 110-240Vac 50/60Hz

Packaging
 2 Boxes
 Box 1: 0,068 x 0,068 x 1,25 m
 Box 2: 0,20 x 0,21 x 0,13 m
 Total Vol 0,0112 m³
 Gross weight 4 Kg Net weight 3 Kg

Notes
 Additional cable length personalisation

Select Electrical connection Surface _23 Built-in XS

1585



Finishes
 ● 11/ _ _ Black (NCS S 8500-N)

LED Colour Temperature
 /1 _ 2700 K CRI >90 726 lm 124 lm/W

Control
 1585 _ _ / _ 1 DALI-2
 1585 _ _ / _ B Push; 1-10V
 1585 _ _ / _ Z Casambi

Materials
 Diffuser: PMMA. Rods: Stainless steel.
 Body: Aluminum. Canopy: ABS.

Light Source and electronics
 2 x LED 3W 175 mA
 Constant current 350 mA
 110-240Vac 50/60Hz

Packaging
 2 Boxes
 Box 1: 0,07 x 0,07 x 1,25 m
 Box 2: 0,51 x 0,51 x 0,16 m
 Total Vol 0,0478 m³
 Gross weight 5,5 Kg Net weight 4 Kg

Notes
 Additional cable length personalisation


Select Electrical connection Surface _23 Built-in XS


1590

Finishes
 ● 11/ _ _ Black
 (NCS S 8500-N)

LED Colour Temperature
 /1 _ 2700 K 
 CRI>90 1152 lm 132 lm/W

Control
 1590 _ _ / _ 1
 DALI-2

 Select
 Eletrical
 connection
 Surface
 _23 Built-in XS



Materials
 Diffuser: PMMA. Rods: Stainless steel.
 Body: Aluminum. Canopy: ABS.

Light Source and electronics
 3 x LED COB 3W 185 mA
 Constant Current 550 mA
 110~240Vac 50/60Hz

Packaging
 2 Boxes
 Box 1: 0,07 x 0,07 x 1,60 m
 Box 2: 0,51 x 0,51 x 0,16 m
 Total Vol 0,0494 m³
 Gross weight 6,5 Kg Net weight 5 Kg

Notes
 Additional cable length
 personalisation

Electrical connection options

Choose your preferred installation option according to your needs.

Drop ceiling

Regular ceiling

_23 Built-in XS



Ø 8 cm
 height 6 cm
 black finish.

Surface



Ø 10 cm
 black finish.

