




















Lampada a sospensione, parete e paletto per esterni IP65 con testa in vetro colato e piattello in alluminio tornito. Paletto in alluminio disponibile in tre altezze, completo di sistema di fissaggio per installazione a terra. Versione parete con braccio rigido di fissaggio a parete. Finiture grigio micaceo, legno verniciato con accessori in ottone satinato, corten. Ideale per hotel, ristoranti, residenze.

Suspension, wall lamp and bollard for outdoor IP65 with cast glass head and turned aluminium plate. Bollard available in three heights, complete with fixing system for ground installation. Wall version with fixed wall arm. Micaceous grey, varnished wood with mat brass accessories and corten finishes are available. Ideal for hotels, restaurants, residences.

	CODICE CODE	FONTI LUMINOSE LIGHT SOURCES	kg
 	 <b>ET04816.045.0201</b> <b>ET04834.045.0201</b> <b>ET04845.045.0201</b>	Potenza assorbita apparecchio / Luminaire power consumption 8W Flusso luminoso apparecchio / Luminaire luminous flux 594lm 2700K Ra>80 220-240V AC ON-OFF  IP65 IK06 	3,43
 	 <b>ET04816.070.0201</b> <b>ET04834.070.0201</b> <b>ET04845.070.0201</b>	Potenza assorbita apparecchio / Luminaire power consumption 8W Flusso luminoso apparecchio / Luminaire luminous flux 594lm 2700K Ra>80 220-240V AC ON-OFF  IP65 IK06 	3,70
 	 <b>ET04816.095.0201</b> <b>ET04834.095.0201</b> <b>ET04845.095.0201</b>	Potenza assorbita apparecchio / Luminaire power consumption 8W Flusso luminoso apparecchio / Luminaire luminous flux 594lm 2700K Ra>80 220-240V AC ON-OFF  IP65 IK06 	3,82
 	<b>YTF04800.012</b>	Tirafondi per il fissaggio al suolo. Anchor bolts for ground fixing.	0,22

# VENEXIA

Matteo Thun 2020

	CODICE CODE	FONTI LUMINOSE LIGHT SOURCES	kg
	<p><b>EL04816.022.0201</b>  <b>EL04819.022.0201</b>  <b>EL04834.022.0201</b></p>	<p>Potenza assorbita apparecchio / Luminaire power consumption 8W                      Flusso luminoso apparecchio / Luminaire luminous flux 594lm                      2700K Ra&gt;80 220-240V AC ON-OFF</p> <p> IP65 IK06 </p>	3,40
	<p><b>EA04816.022.0201</b>  <b>EA04819.022.0201</b>  <b>EA04834.022.0201</b></p>	<p>Potenza assorbita apparecchio / Luminaire power consumption 8W                      Flusso luminoso apparecchio / Luminaire luminous flux 594lm                      2700K Ra&gt;80 220-240V AC ON-OFF</p> <p> IP65 IK06 </p>	3,60

Fotometrie disponibili [www.panzeri.it](http://www.panzeri.it) / Photometric data available at [www.panzeri.it](http://www.panzeri.it)

## CODICI COLORI DISPONIBILI / COLOUR CODES AVAILABLE

**16** corten  
corten

**34** grigio micaceo  
micaceous grey

**45** legno/ottone satinato  
wood/mat brass

**19** ottone satinato  
mat brass



**archiproducts**  
DESIGN AWARDS  
-  
WINNER 2020

