

Knit

Design by Meike Harde


Form, materiality and tangibility collide with the Knit collection. Its texture is magnetic, calling out for us to touch its surface, to feel its warmth and to keep it close. Light seeps outwards through the fabric and downwards through a translucent screen, softening its luminosity.

Pendants




7450

Finishes
● 24/ _ Beige M1
(NCS S 2005-Y50R)

LED temperature colour
/1_ 2700 K 
CRI >90 7470 lm 133,9 lm/W

Control
7450 _ _ / _ 1
DALI
7450 _ _ / _ 3
1-10V
7450 _ _ / _ Z
Casambi

Electrical connection
Surface
_18 Free Wire
_23 Built-in
_31 Remote
Micro
for plaster
ceilings
_32 Remote
XXS
for all types
of drop
ceilings



Materials
Fabric shade: Polyester flame retardant.
Shade: Polyethylene. Difuser: Methacrylate.
Difuser ring: ABS.

Light Source and electronics
6 x LED 5,9W 350 mA
Constant Current 1050 mA
110-240V 50/60Hz

Packaging
1 Box 0,55 x 0,55 x 0,65 m
Vol 0,196 m³
Gross weight 6 Kg Net weight 3,7 Kg

Notes
Extra cable length.


LED  IP20  CE  EAC   Bi-volt

1160 | 10 | /1A | _18 |

Model | Finish | LED temperature colour | Control | Electrical connection | Only for pendants



7455



Finishes
 ● 24/ _ _ Beige M1
 (NCS S 2005-Y50R)

LED temperature colour
 /1_ 2700 K 
 CRI >90 7470 lm 133,9 lm/W

Control
 7455 _ _ / _ 1
 DALI

7455 _ _ / _ 3
 1-10V

7455 _ _ / _ Z
 Casambi

Materials
 Fabric shade: Polyester flame retardant.
 Shade: Polyethylene. Difuser: Methacrylate.
 Difuser ring: ABS.

Light Source and electronics
 6 x LED 5,9W 350 mA
 Constant Current 1050 mA
 110-240V 50/60Hz


Packaging
 1 Box 0,54 x 0,54 x 0,41 m
 Vol 0,119 m³
 Gross weight 5,9 Kg Net weight 3,2Kg

Notes
 Extra cable length.

Electrical connection
 _18 Surface
 _18 Free Wire
 _23 Built-in
 _31 Remote
 _31 Remote
 Micro
 for plaster
 ceilings
 _32 Remote
 _32 Remote
 Micro
 for all types
 of drop
 ceilings

7460



Finishes **24/** _ _ Beige M1 (NCS S 2005-Y50R)

LED temperature colour **/1** _ 2700 K CRI >90 7470 lm 133,9 lm/W

Control **7460** _ _ / _ 1 DALI

7460 _ _ / _ 3 1-10V

7460 _ _ / _ Z Casambi

Materials
Fabric shade: Polyester flame retardant
Shade: Polyethylene Difuser: Methacrylate.
Difuser ring: ABS.

Light Source and electronics
6 x LED 5,9W 350 mA
Constant Current 1050 mA
110-240V 50/60Hz


Packaging
1 Box 0,54 x 0,54 x 0,41 m
Vol 0,119 m³
Gross weight 5,2 Kg Net weight 3,4Kg

Notes
Extra cable length.



Electrical connection
Surface
_18 Free Wire
_23 Built-in
_31 Remote
Micro for plaster ceilings
_32 Remote
XXS for all types of drop ceilings

7470



Finishes **24/** _ _ Beige M1 (NCS S 2005-Y50R)

LED temperature colour **/1** _ 2700 K CRI >90 7470 lm 133,9 lm/W

Control **7470** _ _ / _ 1 DALI

7470 _ _ / _ 3 1-10V

7470 _ _ / _ Z Casambi

Materials
Fabric shade: Polyester flame retardant.
Shade: Polyethylene Difuser: Methacrylate.
Difuser ring: ABS.

Light Source and electronics
6 x LED 6,7W 400 mA
Constant Current 1200 mA
110-240V 50/60Hz


Packaging
1 Box 0,59 x 0,78 x 0,78m
Vol 0,358 m³
Gross weight 9Kg Net weight 5,5Kg

Notes
Extra cable length.



Electrical connection
Surface
_18 Free Wire
_23 Built-in
_31 Remote
Micro for plaster ceilings
_32 Remote
XXS for all types of drop ceilings

7475



Finishes **24/** _ _ Beige M1 (NCS S 2005-Y50R)

LED temperature colour **/1** _ 2700 K CRI >90 7470 lm 133,9 lm/W

Control **7475** _ _ / _ 1 DALI

7475 _ _ / _ 3 1-10V

7475 _ _ / _ Z Casambi

Materials
Fabric shade: Polyester flame retardant
Shade: Polyethylene Difuser: Methacrylate.
Difuser ring: ABS.

Light Source and electronics
6 x LED 6,7W 400 mA
Constant Current 1200 mA
110-240V 50/60Hz

Packaging
1 Box 0,80 x 0,80 x 0,77m
Vol 0,492 m³
Gross weight 9,5Kg Net weight 6Kg

Notes
Extra cable length.



Electrical connection
Surface
_18 Free Wire
_23 Built-in
_31 Remote
Micro for plaster ceilings
_32 Remote
XXS for all types of drop ceilings



Electrical connection options for models 7450 / 7455 / 7460 / 7470 / 7475


Choose your preferred installation option according to your needs. For each composition, the optimal minimum number of drivers will be delivered.

Drop ceiling


The innovative remote and built-in fittings accentuate the silkiness and lightness of compositions on suspended ceilings, its great visual grandeur taking center stage.

For Ref. 7450 / 7455 / 7460 / 7470 / 7475

Remote



Micro \varnothing 3 cm
height 7 cm
for plaster ceilings.
Black finish.




XXS \varnothing 6 cm
height 6 cm
for all types of drop
ceilings. Match with
fixture finish.

Built-in



\varnothing 8 cm
height 6 cm
match with
fixture finish.



Regular ceiling

When architecture does not allow for performance, surface and free wire showcase possibilities for any need or desire with no limits, ideal for both individual or cluster arrangements.

For Ref. 7450 / 7455 / 7460 / 7470 / 7475


Surface




ø 16 cm

match with
fixture finish.


Free Wire



1 wire



2 - 3 wires





4 wires

ø 22 cm

ø 36 cm

ø 40 cm

you can choose the finish of the canopy
among black, white or any colour
matching one of the pendants.



Floor




ø 45 cm

ø 65 cm

ø 65 cm



7480



Finishes ● 24/ _ _ Beige M1 (NCS S 2005-Y50R)
 LED temperature colour /1 _ 2700 K CRI >90 4740 lm 133,9 lm/W


Control 7480 _ _ / _ 5
 Push 7480 _ _ / _ Z
 Casambi

Materials Fabric shade: Textile. Shade: Polyethylene. Difuser: Methacrylate. Difuser ring: ABS Tube: Iron steel. Base: Zamak.
 Light Source and electronics 6 x LED 5,9W 350 mA Constant Voltage 42V 1,43mA 110-240V 50/60Hz

Packaging 2 Boxes Box 1: 0,54 x 0,54 x 0,41 m Box 2: 1,71 x 0,38 x 0,36 m Total Vol. 0,353 m³ Gross weight 21,9 Kg Net weight 11,3 Kg
 Notes Electric cable 2,5 m



7485



Finishes ● 24/ _ _ Beige M1 (NCS S 2005-Y50R)
 LED temperature colour /1 _ 2700 K CRI >90 4740 lm 133,9 lm/W


Control 7485 _ _ / _ 5
 Push 7485 _ _ / _ Z
 Casambi

Materials Fabric shade: Textile. Shade: Polyethylene. Difuser: Methacrylate. Difuser ring: ABS Tube: Iron steel. Base: Zamak.
 Light Source and electronics 6 x LED 5,9W 350 mA Constant Voltage 42V 1,43mA 110-240V 50/60Hz

Packaging 2 Boxes Box 1: 0,54 x 0,54 x 0,41 m Box 2: 1,71 x 0,38 x 0,36m Total Vol. 0,353m³ Gross weight 21,5Kg Net weight 10,8Kg
 Notes Electric cable 2,5 m



7487




Finishes ● 24/ _ _ Beige M1 (NCS S 2005-Y50R)
 LED temperature colour /1 _ 2700 K CRI >90 4740 lm 133,9 lm/W


Control 7487 _ _ / _ 5
 Push 7487 _ _ / _ Z
 Casambi






Materials Fabric shade: Textile. Shade: Polyethylene. Difuser: Methacrylate. Difuser ring: ABS Tube: Iron steel. Base: Zamak.
 Light Source and electronics 6 x LED 5,9W 350 mA Constant Voltage 42V 1,43 mA 110-240V 50/60Hz


Packaging 2 Boxes Box 1: 0,78 x 0,78 x 0,59 m Box 2: 1,93 x 0,45 x 0,46 m Total Vol. 0,7579 m³ Gross weight 30 Kg Net weight 18,5 Kg
 Notes Electric cable 2,5 m









7490	Finishes	LED temperature colour	Control
	● 24/ _ _ Beige M1 (NCS S 2005-Y50R)	/1 _ 2700 K  CRI >90 4740 lm 133,9 lm/W	7490 _ _ / _ 5 Push 7490 _ _ / _ Z Casambi





Materials	Packaging
Fabric shade: Textile Shade: Polyethylene. Difuser: Methacrylate. Difuser ring: ABS. Support: ABS.	1 Box 0,65 x 0,55 x 0,55 m Vol 0,196 m ³ Gross Weight 5,4 Kg Net Weight 3,3 Kg
Light Source and electronics	Notes
6 x LED 5,9 W 350 mA Constant Voltage 42V 1,43 mA 110-240V 50/60Hz	Electric cable 2,5 m
    	






7492	Finishes	LED temperature colour	Control
	● 24/ _ _ Beige M1 (NCS S 2005-Y50R)	/1 _ 2700 K  CRI >90 4740 lm 133,9 lm/W	7492 _ _ / _ 5 Push 7492 _ _ / _ Z Casambi



Materials	Packaging
Fabric shade: Textile. Shade: Polyethylene. Difuser: Methacrylate. Difuser ring: ABS. Support: ABS.	1 Box 0,78 x 0,78 x 0,59 m Vol 0,358 m ³ Gross Weight 7,3 Kg Net Weight 4,5 Kg
Light Source and electronics	Notes
6 x LED 5,9 W 350 mA Constant Voltage 42V 1,43 mA 110-240V 50/60Hz	Electric cable 2,5 m
    	

7494	Finishes	LED temperature colour	Control
	● 24/ _ _ Beige M1 (NCS S 2005-Y50R)	/1 _ 2700 K  CRI >90 4740 lm 133,9 lm/W	7494 _ _ / _ 5 Push 7494 _ _ / _ Z Casambi



Materials	Packaging
Fabric shade: Textile. Shade: Polyethylene. Difuser: Methacrylate. Difuser ring: ABS. Support: ABS.	1 Box 0,80 x 0,80 x 0,75 m Vol 0,48 m ³ Gross weight 9,3 Kg Net weight 5,9 Kg
Light Source and electronics	Notes
6 x LED 5,9 W 350 mA Constant Voltage 42V 1,43 mA 110-240V 50/60Hz	Electric cable 2,5 m
    	

1160 10 /1A
Model Finish
LED temperature colour
Control

