


U-Light

Timo Ripatti



Collezione composta da lampade da parete, soffitto e sospensione in alluminio.
Disponibile in due colori e dimensioni. Sorgente luminosa a LED integrato dimmerabile.
Disponibile con opzione fonoassorbente.

Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

prodotto fonoassorbente / sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy

WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version



wall or ceiling lamp recessed version



acoustic performance

PL UL 1 120 h10 cm canopy
PL UL 2 120 h25 cm canopy

PL UL 1: kg 6,6 m³ 0,180
PL UL 2: kg 7 m³ 0,180

U-LIGHT / h10cm or h25cm ceiling lamp with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
PL	UL 1 120 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 86W - diffused beam 3000K*, 2700K other CCT options available upon request
	UL 2 120 LED (h25 cm)	RU rust brown		


CE IP20 CRI90 ~7736 lm* 90 lm/W* 100-240Vac

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).
Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).


example composition code PL UL1120LED RU XX
Casambi compatibile / Casambi compatible.

KITFAPLULA120AV opzione fonoassorbente avorio / sound absorbing option ivory.
For more information see page 165


This luminaire contains a light source with the energy class F.



rosone standard / standard canopy



altezze disponibili available heights



Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,02	0,15	0,43	0,91	0,84	0,83	0,74	0,56	0,73

CUSTOMER _____ NOTES _____

PL UL _ 120 LED __ XX

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.