

U-Light

Timo Ripatti



Collezione composta da lampade da parete, soffitto e sospensione in alluminio.
Disponibile in due colori e dimensioni. Sorgente luminosa a LED integrato dimmerabile.
Disponibile con opzione fonoassorbente.

Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

prodotto fonoassorbente / sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy


WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version



wall or ceiling lamp recessed version




acoustic performance



SP ULA 160 canopy
SP ULA 160 recessed


canopy kg 9,1 m³ 0,310
recessed kg 4,8 m³ 0,280
Installazione downlight o uplight.
Downlight or uplight mounting.



rosone standard / standard canopy




rosone incasso / recessed canopy



U-LIGHT / suspension with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
SP	ULA 160 LED	AN anthracite grey RU rust brown	XX standard canopy	LED 125W - diffused beam 3000K*, 2700K other CCT options available upon request

CE IP20 CRI90 **LED** ~9025 lm* 72 lm/W* 100-240Vac
Casambi compatibile / Casambi compatible.



U-LIGHT / recessed suspension lamp / DRIVER NOT INCLUDED

Type	Article	Colours	Version	Source
SP	ULA 160 LED	AN anthracite grey RU rust brown	IN recessed canopy	LED 102W - diffused beam 3000K*, 2700K 24VDC other CCT options available upon request

CE IP20 CRI90 **LED** ~9025 lm* 88 lm/W* 24Vdc



foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

example composition code **SP ULA160LED AN IN**
Casambi compatibile / Casambi compatible.

KITFASPULA000AV opzione fonoassorbente avorio / sound absorbing option ivory.
For more information see page 165

Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,11	0,65	2,06	3,63	3,63	3,64	3,45	2,45	3,11

SP ULA 160 LED _____ CUSTOMER _____ NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.