

U-Light

Timo Ripatti



Collezione composta da lampade da parete, soffitto e sospensione in alluminio.
Disponibile in due colori e dimensioni. Sorgente luminosa a LED integrato dimmerabile.
Disponibile con opzione fonoassorbente.

Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

prodotto fonoassorbente / sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy

WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version




wall or ceiling lamp recessed version



acoustic performance

SP ULI 090

kg 7,2 m³ 0,19





U-LIGHT / downward lighting only / DRIVER INCLUDED

Type	Article	Colours	Code End	Source
SP	ULI 090 LED	AN anthracite grey RU rust brown	XX	LED 63W - diffused beam 3000K*, 2700K other CCT options available upon request

CE IP20 CRI90 **LED** ~5158 lm* 82 lm/W* 100-240VAC

example composition code **SP ULI090LED RU XX**

Casambi compatibile / Casambi compatible.



Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,02	0,18	0,57	1,11	1,11	1,15	1,04	0,74	0,93

CUSTOMER	NOTES
SP ULI 090 LED __ XX	

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.