


# STACKING S 30 V RIG - INDOOR

David Rockwell, 2024



LEUCOS



Discover more

REPLACEABLE LED

## TECHNICAL SHEET

MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H30cm [Ø4" H11 3/4"] Canopy: Ø14,5cm H4,6cm [Ø5 3/4" H1 3/4"] Cable length: 300cm [118 1/8"]
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 24V 6,25W (total) 718 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 6,25W (total) 687 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	 
NET WEIGHT	2,7kg



### ⊕ Standard version (supplied with canopy & driver)

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013557
	LED 2700K	0013558
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013858
	LED 2700K	0013859
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013860
	LED 2700K	0013861

### ⊖ Class 3 version installation with remote driver (supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013559
	LED 2700K	0013560
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013814
	LED 2700K	0013815
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013818
	LED 2700K	0013819

We reserve the right to change our product specifications.  
Please visit [www.leucos.com](http://www.leucos.com) for the latest product information