

# U-Light

Timo Ripatti



Collezione composta da lampade da parete, soffitto e sospensione in alluminio.  
Disponibile in due colori e dimensioni. Sorgente luminosa a LED integrato dimmerabile.  
Disponibile con opzione fonoassorbente.

Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

prodotto fonoassorbente / sound absorbing product

COLOURS




WALL AND CEILING LAMP VERSION





PL UL 1 090 h10 cm recessed  
PL UL 2 090 h25 cm recessed

PL UL 1: kg 2,7 m<sup>3</sup> 0,126  
PL UL 2: kg 3,1 m<sup>3</sup> 0,126

U-LIGHT / h10 cm or h25 cm recessed ceiling lamp / DRIVER NOT INCLUDED



rosone incasso / recessed canopy



altezze disponibili available heights

10 cm height

25 cm height

Type	Article	Colours	Version	Source
PL	UL 1 090 LED (h10 cm)	AN anthracite grey	IN recessed canopy	LED 54W - diffused beam 3000K*, 2700K 24VDC  other CCT options available upon request
	UL 2 090 LED (h25 cm)	RU rust brown		

CE IP20 CRI90 LED ~5158 lm\* 95 lm/W\* 24Vdc

foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).  
Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code PL UL1090LED RU IN  
Casambi compatibile / Casambi compatible.

KITFAPLUL090IAV opzione fonoassorbente avorio / sound absorbing option ivory.  
For more information see page 165

This luminaire contains a light source with the energy class F.

Equivalent Sound Absorption Area (A) in m<sup>2</sup> per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,01	0,11	0,32	0,68	0,63	0,63	0,58	0,42	0,54



CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

PL UL \_ 090 LED \_\_ IN \_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Axo Light does not provide legal guarantee for the accuracy of this data sheet.